

Installation Instructions

bend 0 - 45 degrees



Version: 2025-01



Contents

Foreword 3

 Safety..... **Error! Bookmark not defined.**

 Guarantee..... **Error! Bookmark not defined.**

 Disclaimer..... **Error! Bookmark not defined.**

Step 1 – Set the desired angle 4

Step 2 – Clip clamps over the flange..... 4

Step 3 – Screw on the clamps 5

Step 4 – Tape seams 6

Foreword

Safety

- Always observe the safety instructions for the materials and tools to be used.
- Always wear the appropriate personal protective equipment (gloves, safety goggles etc.).
- We would suggest that any roof works is completed by an experienced roofer.
- Always have any electrical works carried out by a certified electrician.
- Please note that the installation works is carried out at your own risk.

Warranty

- Non-electrical components are covered by a 10 year manufacturer's warranty against any manufacturing defects.
- Please retain the original proof of purchase to validate the product warranty.
- Any costs associated to the installation of any replacement parts covered under the warranty remain at the expense of the purchaser.
- Our terms and conditions are available upon request.

Disclaimer

Techcomlight Limited expressly disclaims any liability for any unexpected additional expense arising as a result of condensation or any water damage resulting from condensation, installation not in accordance with Techcomlight Limited's installation guide/s or any other external influences beyond the control of Techcomlight Limited. Techcomlight Limited cannot be held liable for damage to structures caused as a result of making openings and installing the product supplied. Techcomlight assumes no responsibility or obligation for the failure of an architect, contractor, installer or building owner to comply with all applicable laws, ordinances, building codes, energy codes, fire and safety codes and requirements, and adequate safety measures.

Installation instructions reserved. No rights can be derived from this publication.

Step 1 – Set the desired angle

The 2 parts of the 45 degree bend can be put together at any angle from 0 to 45 degrees to make the desired angle.

Step 2 – Clip clamps over the flange

Determine at which angle the two bend parts should fit together. Once the correct angle is set, the 3 supplied clamps can be clipped over the flange (as shown below), so that the 2 parts are temporarily fixed together.

Now remove the protective film from the inside of the bend.

Now install any additional extension tubes, as long as the bend remains accessible afterwards. If not, skip straight to step 3.



Step 3 – Screw on the clamps

When the bend is set at the right angle, the clamps have been fitted, and any other extension tubes have been installed, the clamps can be screwed on permanently with the screws provided.



Step 4 – Tape seams

Now seal all seams including the screwed flange with aluminium tape.

As the 2 parts of the bend have a slightly different diameter, multiple bends can be mounted together by sliding a small diameter end into a large diameter end.



This completes the installation.